

# UPM Prepersonal

Be efficient and produce your exclusive preprinted business documents using woodfree uncoated UPM Preprint papers. Suitable for forms, invoices, statements, letterheads and direct mailing.

## Recommended end-uses

Bespoke forms | Business forms | Correspondence | Direct mailing | Transactional / transpromotional documents

## Product information

Regions	North America
Business contact	<a href="#">UPM Communication Papers</a>
Category	Heatset web offset papers
Grade	Woodfree uncoated (WFU)
Furnish	Hardwood and softwood sulphate pulp
Printing method	B/W inkjet printing   B/W laser printing (dry toner)   Colour laser printing (dry toner)   Offset pre-printing
Format/Size	Reels
Reel diameter (cm)	100,0 - 125,0
Reel width (cm)	17,5 - 250,0
Core (mm)	71,0 / 76,0 / 152,0
Wrapping	Strong moisture proof polyethylene laminated kraft paper
Note	FSC® and PEFC on request but subject to availability.

## Certificates

Product Compliance	EU Ecolabel   94/62 EC Heavy Metal Certificate   BfR Food Certificate   Permanent Paper ISO 9706
Fibre Certificates	FSC Chain-of-Custody   PEFC Chain-of-Custody
Mill Certificates	EES+   EMAS   ISO 9001   ISO 45001   ISO 14001

## Technical target values

Basis weight (ISO 536) (g/m <sup>2</sup> )	50.7	54.1	60.8	67.6
Brightness GE (ISO 2470-2) (%)	93	93	95	95
Opacity TAPPI (T425) (%)	90	91	95	96
CIE Whiteness (ISO 11475)	164	164	164	164
Caliper (mils)	3.7	3.8	4.3	4.8
PPI (pages)	540	525	465	390

Prepersonal material code: 000121

UPM grades (except Blandin) are manufactured to D65 standards. Tappi measurements are estimated values. Blandin manufactured to Tappi specifications.

UPM grades are not manufactured to caliper targets, except as noted. Contact your sales team for more details, or to discuss caliper sensitive applications.

Please note: Technical values are informative and subject to production variations.